


150W Single Output Switching Power Supply



- AC input range selectable by switch
- Protections: Short circuit / Overload / Over voltage
- Fixed switching frequency at 25KHz
- Approvals: UL / CUL / TUV / CB / CE / BSMI
- Cooling by free air convection
- 100% full load burn-in test
- 2 years warranty

CASE: 906

199x 110x 50 mm

AC input voltage range..... 88~132VAC / 176~264VAC selectable by switch
 DC adjustment range..... $\pm 10\%$ rated output voltage
 Overload protection..... 105%~150% shut off, AC recycle to re-start
 Over voltage protection..... 115%~145% rated output voltage
 Setup, rise, hold up time.... 100ms, 50ms, 28ms at full load and 230VAC
 Withstand voltage..... I/P-O/P:3KVAC, I/P-FG:1.5KVAC, 1minute
 Working temperature..... -10~60°C (refer to output derating curve)
 Safety standards..... UL1012, UL60950-1, TUV EN60950-1 approved
 EMC standards..... EN55022 class B, EN61000-3-2,-3
 EN61000-4-2,3,4,5,6,8,11, ENV50204
 Connection..... 7P/ 9.5mm pitch terminal block
 Packing..... 0.8kg ; 16pcs / 13.8kg / 0.95CUFT

Stock No.	Model No.	Output	Tol.	R&N	Effi.
10081	S-150-5	5V, 0~30A	$\pm 2\%$	150mV	78%
10082	S-150-7.5	7.5V, 0~20A	$\pm 1\%$	150mV	80%
10083	S-150-9	9V, 0~16.7A	$\pm 1\%$	180mV	80%
10084	S-150-12	12V, 0~12.5A	$\pm 1\%$	180mV	82%
10088	S-150-13.5	13.5V, 0~11.2A	$\pm 1\%$	180mV	83%
10085	S-150-15	15V, 0~10A	$\pm 1\%$	180mV	84%
10086	S-150-24	24V, 0~6.5A	$\pm 1\%$	240mV	85%
10089	S-150-27	27V, 0~5.6A	$\pm 1\%$	240mV	86%
10087	S-150-48	48V, 0~3.2A	$\pm 1\%$	240mV	87%